

API 17H Hotstab & Receptacle

Cetrax Systems Ltd., Silverfield House, Claymore Drive, Aberdeen AB23 0LT

Tel: +44 (0)1224 827999 ~ Fax: +44 (0)1224 828001 ~ email: info@cetrax.com ~ web: www.cetrax.com



Conforms to API 17H and ISO 13628-8 standards

The male stabbed is fitted with two pilot operated check valves as part of the main body. The check valves minimise oil leakage and water ingress and prevent under pressure in the hoses.

The female receptacle is manufactured as a flange mount or flush mount unit. The receptacle is easily mounted using 4 bolts.

Specifications

Standard Working Pressure	207 Bar (3,000 psi), Higher Pressures Available upon request
Weight	4.5 Kg (Dual Port male stab with handle) 5.0 Kg (Dual Port receptacle w/o flange) 4.0 Kg (Single Port male stab with handle) 3.5 Kg (Single Port receptacle w/o flange)
Port Sizes	All Ports 3/8" NPT Other sizes of ports available upon request
Handle Type	T-Handle on male stab as standard Other handles available upon request
Material	Stainless Steel 316L (Stab and Receptacle) POM (Dummy Stab)

Options

Male Stab Handles	Client Preference Available Upon Request
Working Pressure	Higher Pressure Ratings Available Upon Request
Materials	Client Preference Materials Available Upon Request